

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : <b>H04Q 7/38</b>		(11) International Publication Number: <b>WO 00/19758</b>
<b>A2</b>		(43) International Publication Date: 6 April 2000 (06.04.00)
(21) International Application Number: <b>PCT/EP99/07066</b>		(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 23 September 1999 (23.09.99)		
(30) Priority Data: 982071 25 September 1998 (25.09.98) FI		
(71) Applicant (for all designated States except US): TELEFONAKTIEBOLAGET LM ERICSSON (publ) [SE/SE]; SE-126 25 Stockholm (SE).		
(72) Inventors; and (75) Inventors/Applicants (for US only): GARCIA-MARTIN, Miguel-Angel [ES/ES]; Pase Esperanza 8, esc. 3, 7-B, E-28005 Madrid (ES). GARCIA GONZALES, Juan, Maria [ES/ES]; Banos de Montemayor 6, 1 B, E-28005 Madrid (ES).		
(74) Agent: BORENIUS & CO OY AB; Kansakoulukuja 3, FIN-00100 Helsinki (FI).		Published Without international search report and to be republished upon receipt of that report.

(54) Title: SIGNALLING IN A TELECOMMUNICATIONS SYSTEM

(57) Abstract

A method of transmitting signalling information in a Public Land Mobile Network (PLMN) between a pair of peer application parts. An adaptation layer is interposed between the TCAP of an SS7 network and a TCP/IP part to allow signalling data to be transmitted to and from an application part via an IP based network. The Adaptation layer provides for translation between global titles or Destination Point Codes (DPCs), used as the basis for addressing in the SS7 network, and IP addresses/port numbers for use in the IP network. The adaptation layer also provides for formatting of messages suitable for processing by the TCP/IP layers, and also for formatting signalling information flowing in the reverse direction.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## Signalling in a Telecommunications System

### Field of the Invention

- 5 The present invention relates to signalling in a telecommunications system and in particular, though not necessarily, to the transmission of signalling data in a Public Land Mobile Network.

### 10 Background to the Invention

- In a telecommunications system, signalling equipment and signalling channels are required for the exchange of information between system elements or nodes. In  
15 particular, this internode signalling informs the nodes of what is to be performed when a telephone or data call is to be set up or released in so-called "circuit-switched" connections. Signalling is also often used to communicate information on the status of the system and  
20 of individual subscribers.

- Modern telecommunications systems now largely make use of Common Channel Signalling (CCS) whereby signalling information is transmitted on one or more dedicated  
25 signalling channels, distinct from the channels used to carry actual user information (e.g. voice or data). An important feature of CCS is that the same signalling system may support services in a variety of existing telecommunications networks, e.g. Public Switched  
30 Telephone Network (PSTN), Integrated Services Digital Network (ISDN), and Public Land Mobile Networks (PLMN), as well as proposed future protocols such as B-ISDN, enhancing greatly the interoperability of networks supporting different protocols.

35

CONFIRMATION COPY

Currently, the predominant CCS is known as Signalling System Number 7 (SS7), defined in the ITU-T (International Telecommunications Union - Technical) recommendations starting with Q.700. SS7 is a packet switched system occupying one time slot per frame of the Time Division Multiple Access (TDMA) E.1 or T.1 transmission formats (the other time slots being available for user voice or data information). Individual signalling message packets (referred to as Message Signalling Units or MSUs) are associated with respective individual telephone calls. As only a relatively small amount of signalling information is associated with a single telephone call, a single SS7 channel is able to handle all signalling between two network nodes (termed "signalling points") for several thousands of calls. It is noted that the route taken by an MSU in the SS7 network may be the same as that over which the associated telephone call is established, or it may be different.

As already noted, SS7 (along with other CCS systems) is able to support a number of different telecommunications networks (e.g. PSTN, ISDN, PLMN). In signal processing terms, SS7 comprises a Message Transfer Part (MTP) which deals with the physical transfer of signalling information over the signalling network (MTP layer 1), message formatting, error detection and correction, etc (MTP layer 2), and message routing (MTP layer 3). SS7 also comprises user parts and application parts which allow several "users" (i.e. ISDN User Part, Telephony User Part, Mobile Application Part, etc) to send signals in the same signalling network.

Figure 1 illustrates a PLMN (GSM) having a Gateway Mobile Switching Centre (GMSC) 1 which provides an interface for the PLMN to "foreign" networks such as

ISDNs, PSTNs, and other PLMNs. An exemplary Mobile Station (MS), registered to the PLMN, is indicated by the reference numeral 2. A number of exemplary nodes within the PLMN are also shown including: the GMSC 1; a  
5 Mobile Switching Centre (MSC) 3; a Base Station Controller (BSC) 4; a Base Transceiver Station (BTS) 5; an Intelligent Network node (IN) 6; a Visitor Location Register (VLR) 7; a Home Location Register (HLR) 8; an Authentication Centre (AUC) 9; and an Equipment Identity  
10 Register (EIR) 10. A more complete description of a PLMN, and other aspects of telecommunication networks, is given in "Understanding Telecommunications", vols. 1 & 2, Studentlitteratur, Lund, Sweden (ISBN 91-44-00214-9).

15

Figure 1 indicates the various signalling interfaces which are used to signal between the network nodes detailed above. These interfaces include: the ISUP/TUP interfaces between the GMSC 1 and the foreign networks;  
20 the INAP interface used between the MSC 3 and Intelligent Network (IN) nodes; the MAP interface used between the MSC/GMSC 1,3 and PLMN specific nodes (VLR, HLR, AUC, EIR) 6-10; the BSSMAP used between the MSC 3 and the BSC 4; and the Abis interface between the BSC 4  
25 and the BTS 5. Conventionally, all of these interfaces serve as user parts and application parts of an SS7 network, residing above the MTP layers. The resulting protocol stacks are illustrated in Figure 2.

30 In order to provide the INAP and MAP (as well as certain other application parts, e.g. OMAP, which also rely upon connectionless communication over the signalling network) with certain functions and protocols as well as a standard and common interface between the application  
35 parts and the network signalling service, a Transaction Capabilities Application Part (TCAP or TC) is interposed

between these application parts and the MTP.

Furthermore, a Signalling Connection and Control Part (SCCP) is interposed between the TCAP and the MTP for controlling the signalling connection. The SCCP is also used by certain other application parts (referred to as SCCP users, e.g. BSSMAP) which do not use the services of the TCAP and which rely upon connection-oriented and/or connectionless communication over the signalling network.

SS7 makes use of addresses known as Destination Point Codes (DPCs) to route signalling data through the "visibility area" of a telecommunications network, the visibility area typically being the network itself together with the interfaces between the network and "foreign" networks under the control of other operators.

A DPC is placed in the header of an MSU and is examined by a network signalling point (SP) upon receipt of the MSU to determine the next hop for the MSU en route to its destination. So-called Subsystem Numbers (SSNs) are used by SS7 to direct data to specific application parts (see below) and are also included in MSUs.

With reference to Figure 2, it is noted that routing between various application parts above the SCCP layer is achieved using so-called "global titles". A global title contains (amongst other things) a number dialled in the PLMN or the number of a roaming mobile station (for the specific example shown in Figure 1). The SCCP contains all the network and routing information required to analyse a global title and translate it into a DPC and, optionally, a Subsystem Number (SSN) which identify the next or final signalling point in the SS7 network.

- In an SS7 network, any change in the DPC allocation within the visibility area requires the operator to update the DPC database (or routing table) which exists in each SP of the network. This however adds
- 5 significantly to the maintenance overheads of the network. The dedicated nature of SS7 makes it in general expensive to install and maintain (in relation to both hardware and software), a significant barrier especially to prospective new telecom operators.
- 10 Furthermore, as an SS7 network occupies bandwidth on TDMA frames of the E.1/T.1 transmission protocols (one slot per time frame), the bandwidth available for actual user call data is restricted. Yet another disadvantage of traditional signalling architectures is that the
- 15 interoperability of SS7 networks is limited due to the dedicated nature of the MTP physical layers.

#### Summary of the Present Invention

- 20 It is an object of the present invention to overcome or at least mitigate the above noted disadvantages of existing telecommunication signalling systems.

- According to a first aspect of the present invention
- 25 there is provided a method of transmitting signalling information in a telecommunications network between a pair of application parts, the method comprising;
- generating said signalling information at a first of said application parts, including addressing
- 30 information associated with the second of the application parts;
- passing said signalling information from the application part to a Transaction Capabilities Application Part (TCAP);
- 35 passing said signalling information from the TCAP to an adaptation layer arranged to determine an IP

address and port number associated with said addressing information;

passing said signalling information and said IP address and port number to an Internet Protocol (IP) part and transmitting the signalling information over an  
5 IP network to said destination IP address in one or more IP datagrams;

decapsulating said signalling information at the destination associated with the IP address and at an  
10 adaptation layer identified by said port number; and routing the signalling information to the second user part.

The use of the IP based network for transmitting  
15 signalling information reduces the need for conventional signalling infrastructure (although this may still be used in part). IP based networks offer increased flexibility (e.g. routers of the network have self-updating routing tables) and reduced operating,  
20 maintaining, and engineering costs in comparison with conventional telecommunications signalling networks.

It will be appreciated that the Signalling Connection and Control Part (SCCP), which is normally interposed  
25 between the TCAP and the MTP in an SS7 network, is omitted from the present invention in so far as it relates transmitting signalling information from the TCAP to an IP part. Rather, the adaptation layer interfaces the TCAP to the IP part. SCCP is designed to  
30 segment signalling messages into 272 octet blocks, such as are required by the MTP of SS7. In contrast, individual TCP and UDP datagrams are capable of carrying a much larger number of octets than an MTP message. Thus, by omitting the SCCP, the present invention avoids  
35 unnecessary segmentation of signalling messages.



The method of the present invention is particularly applicable to Public Land Mobile Networks (PLMN), where said pair of application parts may be, for example, peer Mobile Application Parts (MAPs) or Intelligent Network Application Parts (INAPs) present at respective signalling nodes of the PLMN.

In certain embodiments of the invention, the adaptation layer performs a translation between a Destination Point Code (DPC) and an associated IP address and port number. In other embodiments however, the IP address and port number are obtained at the adaptation layer directly from a global title provided as part of the addressing information from the application part.

Preferably, the adaptation layer is arranged to provide all service functionality that the TCAP would otherwise receive from a SCCP including sequence control, return on error, and congestion control.

Preferably, the adaptation layer is arranged to encapsulate signalling and addressing information into a form suitable for further processing by the IP part.

Preferably, the signalling information is passed from the adaptation layer to the IP part via a UDP or TCP encapsulating layer. More preferably, the adaptation layer is arranged to encapsulate signalling and addressing information into a form suitable for further processing by the UDP or TCP layers.

According to a second aspect of the present invention there is provided apparatus for transmitting signalling information in a telecommunications network between a pair of application parts, the apparatus comprising; generating means for generating said signalling information at a first of said application parts,

including addressing information associated with the second of the application parts;

a Transaction Capabilities Application Part (TCAP) for receiving said signalling information;

5 an adaptation layer arranged to receive said signalling information from the TCAP and to determine an IP address and port number associated with said addressing information;

10 an Internet Protocol (IP) part arranged to receive said signalling information and said IP address and port number and to transmit the signalling information over an IP network to said destination IP address in one or more IP datagrams;

15 processing means at the destination associated with the IP address and at an adaptation layer identified by the port number, arranged to decapsulate said signalling information; and

routing means arranged to route the signalling information to the second user part.

20

According to a third aspect of the present invention there is provided a gateway node for coupling signalling information from a common channel signalling (CCS) network of a telecommunications system, to an Internet Protocol (IP) based network, the gateway node  
25 comprising:

a Message Transfer Part (MTP) arranged to receive signalling information over the CCS network;

30 a Signalling Connection Control Part (SCCP) arranged to receive said signalling information from the MTP whilst controlling the signalling connection over the CCS network;

an adaptation layer arranged to receive said signalling information from the SCCP and to determine an  
35 IP address and port number associated with a global title or Destination Port Code (DPC) included in the signalling information;

an IP layer for receiving the signalling information and the IP address and port number from the adaptation layer and for arranging for transmission of the signalling information over the IP based network in the form of IP datagrams.

#### Brief Description of the Drawings

For a better understanding of the present invention and in order to show how the same may be carried into effect reference will now be made, by way of example, to the accompanying drawings, in which:

Figure 1 illustrates schematically a GSM network together with the signalling protocols used therein;

Figure 2 illustrates schematically the signal processing layers of an SS7 protocol of the network of Figure 1;

Figure 3 illustrates schematically the use of a TCP/IP network to transmit signalling information in a telecommunications network; and

Figure 4 illustrates signalling protocol layers present at nodes of the telecommunications network of Figure 3.

#### Detailed Description of Certain Embodiments

The general structure in terms of signalling nodes and signalling interfaces of a GSM PLMN has already been described above with reference to Figures 1 and 2.

Figure 3 shows various nodes of the GSM PLMN where it is assumed, for the purpose of this discussion, that each of these nodes comprises an application part (e.g. MAP, INAP) having a conventional composition such that it can be supported by SS7 for the sending of signalling information to a peer application part at some other node. Considering in particular the MSCs 3a, 3b and the GMSC 1, these nodes are connected to a conventional SS7

network 11 for the purpose of communicating signalling information.

Intelligent network and PLMN specific nodes, including the IN node 6, VLR 7, HLR 8, AUC 9, and EIR 10, each have application parts (and in particular MAP and INAP) similarly constructed for peer-to-peer communication via SS7. However, these nodes each comprise an additional interface which enables them to communicate signalling information via an IP network 12. In order to enable interworking of the SS7 connected nodes and the IP network connected nodes, the two signalling networks 11,12 are connected by a gateway node 13.

Figure 4 shows schematically the protocol layers present at a node connected to the IP network 12 (Node 1), at the gateway node 13 (Node 2), and at a node connected to the SS7 network 11 (Node 3). Of the layers shown, the INAP/MAP, TCAP, SCCP, TCP/IP, physical layer, and MTP are substantially conventional in structure and therefore will not be described in detail. Rather, the reader should make reference to the literature including "Understanding Telecommunications", vols. 1 & 2, Studentlitteratur, Lund, Sweden (ISBN 91-44-00214-9), and the ITU-T (International Telecommunications Union - Technical) recommendations starting with Q.700 which define Signalling System Number 7 (SS7). The present discussion is concerned in the main with the Adaptation layer which enables the TCP/IP and physical layers to replace the MTP (and SCCP), such that the TCAP can communicate over the IP network 12.

As has already been discussed above, MSUs are routed in an SS7 network using Destination Point Codes (DPCs) which are attached to each of the MSUs. Within a signalling point, messages are directed to a specific

application (e.g. HLR, VLR, etc) on the basis of a Subsystem Number (SSN) also attached to the MSU. On the other hand, datagrams in an IP network are routed to a destination machine on the basis of an IP address, and to an application running on a particular machine on the basis of an IP port number. A main function of the Adaptation layer therefore is to translate between global titles and IP addresses and port numbers, a process which is achieved using a database associating global titles and IP addresses/port numbers.

At Node 1, for signalling data to be transmitted to Node 3, the adaptation layer determines an IP address and port number associated with a global title contained in the message "primitive" received from the TCAP. The Adaptation layer then encapsulates the primitives into a format which is acceptable to the TCP (or UDP) layer before passing the information to the TCP (or UDP) layers. A further function of the Adaptation layer is to monitor the state of the connection between the two communicating peer application parts. For example, if communication between the application parts breaks down, and cannot be re-established, then the Adaptation layer may report this to the TCAP. It will be appreciated that the Adaptation layer communicates with the TCAP in a manner identical to that of the SCCP (which is omitted).

The TCP/UDP layers pass the encapsulated signalling information to the IP layer. The messages transmitted over the IP network 12 have the following structure:

Physical header	IP header	TCP header	Addresses Global title/DPC /SSN	TCAP header	INAP/MAP data
-----------------	-----------	------------	---------------------------------------	-------------	---------------

At the gateway node 13 (Node 2 in Figure 4), the Adaptation layer lies above the IP network and SS7 network side layers. The adaptation layer provides for decapsulation of the received message and passes it to  
5 the SCCP on the SS7 network side for further processing.

The messages received by the SCCP from the adaptation layer contain either a global title or a DPC/SSN or both. In the case that the message contains only a  
10 global title, then the SCCP translates that titles into a DPC/SSN as already described above. For transmission over the SS7 network 11, the SCCP passes the primitives, with associated DPCs, to the MTP which handles transmission in a known manner. Similarly, the protocol  
15 layers at the receiving node (Node 3) correspond to the conventional SS7 structure.

It will be appreciated by the skilled person that various modifications may be made to the above described  
20 embodiment without departing from the scope of the present invention. For example, the connectivity of the network nodes shown in Figure 3 may be varied, such that certain IN nodes are connected to the SS7 network, whilst the MSCs and/or the GMSC may be connected to the  
25 IP network. It may also be the case that nodes are connected to both the SS7 network and the IP network, such that one network provides a back-up for the other network.

30 It will also be appreciated that in the event that the TCAP provides addressing information to the adaptation layer which includes a DPC/SSN, rather than just a global title, then the adaptation layer may translate between the DPC and the IP address/port number.

35

Claims

1. A method of transmitting signalling information in a telecommunications network between a pair of application parts, the method comprising;
  - generating said signalling information at a first of said application parts, including addressing information associated with the second of the application parts;
  - 10 passing said signalling information from the application part to a Transaction Capabilities Application Part (TCAP);
  - passing said signalling information from the TCAP to an adaptation layer arranged to determine an IP address and port number associated with said addressing information;
  - 15 passing said signalling information and said IP address and port number to an Internet Protocol (IP) part and transmitting the signalling information over an IP network to said destination IP address in one or more IP datagrams;
  - decapsulating said signalling information at the destination associated with the IP address and at an adaptation layer identified by said port number; and
  - 25 routing the signalling information to the second user part.
2. A method according to claim 1 for use in a Public Land Mobile Network (PLMN), where said pair of application parts are peer Mobile Application Parts (MAPs) or Intelligent Network Application Parts (INAPs) present at respective signalling nodes of the PLMN.
3. A method according to claim 1 or 2 and comprising
- 35 passing addressing information from the TCAP to the adaptation layer which includes a global title.

4. A method according to any one of the preceding claims and comprising passing addressing information from the TCAP to the adaptation layer which includes a  
5 Destination Point Code and optionally a Subsystem Number.
5. A method according to any one of the preceding claims, wherein the adaptation layer provides all  
10 service functionality that the TCAP would otherwise receive from a SCCP including sequence control, return on error, and congestion control.
6. A method according to any one of the preceding  
15 claims and comprising passing the signalling information from the application part to the adaptation layer via a Transaction Capabilities Application Part.
7. A method according to any one of the preceding  
20 claims, wherein the adaptation layer encapsulates signalling and addressing information into a form suitable for further processing by a UDP/TCP layer disposed between the adaptation layer and the IP part.
- 25 8. Apparatus for transmitting signalling information in a telecommunications network between a pair of application parts, the apparatus comprising;  
generating means for generating said signalling information at a first of said application parts,  
30 including addressing information associated with the second of the application parts;  
a Transaction Capabilities Application Part (TCAP) for receiving said signalling information;  
an adaptation layer arranged to receive said  
35 signalling information from the TCAP and to determine an IP address and port number associated with said addressing information;



an Internet Protocol (IP) part arranged to receive said signalling information and said IP address and port number and to transmit the signalling information over an IP network to said destination IP address in one or  
5 more IP datagrams;

processing means at the destination associated with the IP address and at an adaptation layer identified by the port number, arranged to decapsulate said signalling information; and

10 routing means arranged to route the signalling information to the second user part.

9. A gateway node for coupling signalling information from a common channel signalling (CCS) network of a telecommunications system, to an Internet Protocol (IP)  
15 based network, the gateway node comprising:

a Message Transfer Part (MTP) arranged to receive signalling information over the CCS network;

a Signalling Connection Control Part (SCCP)  
20 arranged to receive said signalling information from the MTP whilst controlling the signalling connection over the CCS network;

an adaptation layer arranged to receive said signalling information from the SCCP and to determine an  
25 IP address and port number associated with a global title or Destination Port Code (DPC) included in the signalling information;

an IP layer for receiving the signalling information and the IP address and port number from the  
30 adaptation layer and for arranging for transmission of the signalling information over the IP based network in the form of IP datagrams.




Figure 1






Figure 2

Figure 3Figure 4




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>H04Q 3/00</b>	<b>A3</b>	(11) International Publication Number: <b>WO 00/19758</b> (43) International Publication Date: <b>6 April 2000 (06.04.00)</b>
(21) International Application Number: <b>PCT/EP99/07066</b> (22) International Filing Date: <b>23 September 1999 (23.09.99)</b> (30) Priority Data: <b>982071</b> <b>25 September 1998 (25.09.98)</b> <b>FI</b> (71) Applicant (for all designated States except US): <b>TELEFONAK- TIEBOLAGET LM ERICSSON (publ) [SE/SE]; SE-126 25 Stockholm (SE).</b> (72) Inventors; and (75) Inventors/Applicants (for US only): <b>GARCIA-MARTIN, Miguel-Angel [ES/ES]; Pase Esperanza 8, esc. 3, 7-B, E-28005 Madrid (ES). GARCIA GONZALES, Juan, Maria [ES/ES]; Banos de Montemayor 6, 1 B, E-28005 Madrid (ES).</b> (74) Agent: <b>BORENIUS &amp; CO OY AB; Kansakoulukuja 3, FIN-00100 Helsinki (FI).</b>	(81) Designated States: <b>AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</b> Published <i>With international search report.</i> (88) Date of publication of the international search report: <b>8 September 2000 (08.09.00)</b>	

(54) Title: **SIGNALLING IN A TELECOMMUNICATIONS SYSTEM**

## (57) Abstract

A method of transmitting signalling information in a Public Land Mobile Network (PLMN) between a pair of peer application parts. An adaptation layer is interposed between the TCAP of an SS7 network and a TCP/IP part to allow signalling data to be transmitted to and from an application part via an IP based network. The Adaptation layer provides for translation between global titles or Destination Point Codes (DPCs), used as the basis for addressing in the SS7 network, and IP addresses/port numbers for use in the IP network. The adaptation layer also provides for formatting of messages suitable for processing by the TCP/IP layers, and also for formatting signalling information flowing in the reverse direction.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/EP 99/07066

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04Q3/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 853 411 A (LUCENT TECHNOLOGIES INC) 15 July 1998 (1998-07-15) column 2, line 21 -column 4, line 40 column 8, line 40 -column 9, line 8	1,6-9
X	US 5 793 771 A (DARLAND TIMOTHY E ET AL) 11 August 1998 (1998-08-11) column 2, line 20 -column 3, line 55 claims 1-20	1,6-9
A	WO 98 28885 A (ERICSSON TELEFON AB L M) 2 July 1998 (1998-07-02) page 2, line 16 - line 26 claims 1-14	1-9
-/-		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

15 June 2000

Date of mailing of the international search report

26/06/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Chassatte, R

Form PCT/ISA/210 (second sheet) (July 1992)

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/07066

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	SEVCIK M ET AL: "CUSTOMERS IN DRIVER'S SEAT: PRIVATE INTELLIGENT NETWORK CONTROL POINT" PROCEEDINGS OF THE INTERNATIONAL SWITCHING SYMPOSIUM, DE, BERLIN, VDE VERLAG, vol. SYMP. 15, 1995, pages 41-44, XP000495622 ISBN: 3-8007-2093-0 abstract paragraph '02.1! - paragraph '02.2!	1-9
A	EP 0 781 020 A (ERICSSON GE MOBILE INC) 25 June 1997 (1997-06-25) the whole document	

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/07066

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0853411 A	15-07-1998	US 6011803 A	04-01-2000
		CA 2222773 A	13-07-1998
		DE 69700201 D	02-06-1999
		DE 69700201 T	02-09-1999
		JP 10294768 A	04-11-1998
US 5793771 A	11-08-1998	CA 2258597 A	31-12-1997
		EP 0917786 A	26-05-1999
		WO 9750217 A	31-12-1997
WO 9828885 A	02-07-1998	AU 5352098 A	17-07-1998
		CN 1247659 A	15-03-2000
		EP 0958684 A	24-11-1999
		NO 992963 A	20-08-1999
		SE 9604784 A	21-06-1998
EP 0781020 A	25-06-1997	US 5737517 A	07-04-1998

Form PCT/ISA/210 (patent family members) (July 1992)